

PRESSURE PIPE

LIMITLESS OPTIONS TO FIT EXACTING NEEDS

The uses for cold-drawn seamless steel pipe are limitless, and MST is ready to meet every demanding operational requirement and precise specification. Our cold-drawn seamless pipe is available in many steel grades and specifications, and MST can provide the high-quality product that meets your needs exactly, even custom sizes that are not based on a standard pipe schedule. UV coating is always available on any of our cold-drawn seamless steel products.

Size Range: Cold-drawn seamless pipe is available in a wide variety of sizes, from 1/2" to 4" IPS (12.7mm to 101.6mm IPS). We offer single random, double random or custom-cut lengths. We also have the flexibility to offer non-standard pipe sizes. Custom made pipe sizes and lengths are standard practice at MST. If you have a size not found on a standard IPS pipe schedule, no problem. If you need a specific cut length, no problem. We can cut anywhere from 10' to 52' based on the size and pipe that you are inquiring about.

We Offer:

- Non-standard sizes and made-to-order
- Custom bundle sizes
- Emergency repair
- Quick turnaround
- Expedited deliveries
- Melted and manufactured in the USA
- Pickled, oiled, plugged
- UV Coating
- Min mill quantities: 2000# for pressure pipe

IT'S ABOUT TIME.

Specifications:

A53, A106 Grade A, B & C

A333 Grade 1 & 6

A335 P1, P2, P5, P9, P11, P12, P22, P23, P91

MST also is one of just a handful of manufacturers globally – and the only one domestically – that offers NCA-3800 nuclear capabilities.

IPS SIZE		OD	WALL	WT/FT
1/2	40	.840	.109	.851
	80		.147	1.088
	160		.188	1.309
	XXHY		.294	1.714
3/4	40	1.050	.113	1.131
	80		.154	1.474
	160		.219	1.944
	XXHY		.308	2.441
1	40	1.315	.133	1.679
	80		.179	2.172
	160		.250	2.844
	XXHY		.358	3.659
1-1/4	40	1.660	.140	2.273
	80		.191	2.997
	160		.250	3.765
	XXHY		.382	5.214
1-1/2	40	1.900	.145	2.718
	80		.200	3.631
	160		.281	4.859
	XXHY		.400	6.408
2	40	2.375	.154	3.653
	80		.218	5.022
	160		.344	7.462
	XXHY		.436	9.029
2-1/2	40	2.875	.203	5.793
	80		.276	7.661
	160		.375	10.01
	XXHY		.552	13.69
3	40	3.500	.216	7.576
	80		.300	10.25
	160		.438	14.32
	XXHY		.600	18.58
3-1/2	40	4.000	.226	9.109
	80		.318	12.50
	XXHY		.636	22.850
	4		40	4.500
80		.337	14.983	
160		.531	22.509	
XXHY		.674	27.541	

